

GAP WaterGuard Self-Adhered MetalGuard HT

(Metal and Tile High Temperature)

Product Description

GAP WaterGuard Self-Adhered MetalGuard HT is a SBS modified high temperature rated, fiberglass reinforced roofing underlayment. Ideal for metal & tile roofing and offers great wind-uplift properties, eve, valley and ice damming protection. Temperature rating of 40°F and has a high temperature rating of 250°F. The overall thickness is 60 mil nominal (ASTM D1777), 36" (width) x 67' (length), 2 square roll, weight approximately 68 lb. per roll, shrink bagged for easy storage and handling.

Features and Benefits

- ✓ **Unique "textured" slip resistant surface** – *greater feeling of safety and security while walking*
- ✓ **Metal and Tile applications** – *ideal for metal and mechanically attached tile*
- ✓ **Exceptional SBS rubberized adhesive backing** – *unique modified bitumen with wide temperature installation range and great nail/screw seal ability*
- ✓ **Highly pliable fiberglass mat reinforcement** – *conforms easily to valleys, corners and angles*
- ✓ **120-day UV exposure** – *longer dry-in time and greater protection from temporary exposure*
- ✓ **Meets ASTM D1970 testing and the 60 mil thickness** – *no concerns with code enforcement and significant "body" for assured performance and nail sealability*
- ✓ **Made in the USA** – *assured performance, safe components and US quality standards (no coal tar!)*
- ✓ **2 square rolls** – *easy to handle and install with a strong split release poly liner.*



Key Technical Details

Government Code Compliance **FBC# FL22853.1**
High Velocity Hurricane Zone (HVHZ)
(Miami and Dade Counties)

Data (ASTM Specification D1970)

Rolls/Pallet	20
Weight/Roll	68 lbs (nominal)
Width	36"
Length	67'
Thickness (ASTM D1777)	60 Mils (nominal)
Coverage	2 Square (201 square Feet)
Perm Rating	<0.1 U.S. perms

Additional ratings (ASTM Specification D1970)

Adhesion to plywood, min at 40°F 2.0 lb/ft width	Pass
Adhesion to plywood, min at 75°F 12.0 lb/ft width	Pass
Flexibility temperature -20° F	Pass
Moisture Vapor Permeance	0.1 U.S. perms
Seal ability around nail	No leaks, Pass
Waterproof integrity after low temp flexibility	No leaks, Pass
Waterproof integrity of lap seam	No leaks, Pass
Packaging	Shrink Bag
Manufacturing Location	U.S.A.



**Roofing runs
in our blood!**

Still Family founded owned after 3 generations!

Note: We believe that the above statements are reliable and should be used for general guidance purposes only and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for purpose. There is no warrant of fitness for a purpose. Our standard terms and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products or publications. These data should not be considered a specification.

GAP Roofing Inc., 4444 Hunt Street, Pryor, OK 74361 (918) 825-5200