



Product Technical Data Sheet

GAP Roofing Self-Adhered SBS Base Sheet

Description: GAP Roofing Self-Adhered SBS Base sheet is a flexible, fiberglass mat, SBS modified, self-adhering modified asphalt sheet with a polyolefin film on the surface and a removable treated film on the adhesive side. Available also in sand.

Uses: GAP Roofing SA Base is used in GAP Roofing systems along with the SA Cap Sheet Rolled Roofing. SA Base can be easily applied by removing the split release film from the adhesive side and pressing the base sheet's self-adhesive back surface into place.

Physical Properties:

Rolls/Pallet	Data
Weight/Roll	20
Width	70 lbs (nominal)
Thickness	39 3/8"
Coverage	55 Mils (nominal)
	2 Square

Other Properties

Maximum Load @ 0°F MD/CD, min	75 lbf/in	Pass
Elongation @ 0°F	2%	Pass
Maximum Load @ 74°F MD/CD, min	35 lbf/in	Pass
Elongation @ 74°F	10%	Pass
Tear Strength @ 74°F	160 lbf	Pass
Adhesion to plywood, min at 75 F	20.0 lbf/ft width	Pass
Flexibility temperature	0° F	Pass

Note: We believe that the above statements are reliable and should be used for general guidance purposes only and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for purpose. There is no warrant of fitness for a purpose. Our standard terms and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products or publications. These data should not be considered a specification.